

# RTL 3



Two bass units within these 'reflex transmission' line loudspeakers further enhance bass performance, contributing to increased sensitivity and additional power handling. The TDL RTL 3 is the perfect partner for a larger room. Retaining the fine stereo imagery of their smaller counterparts, room position is not critical, neither are they difficult to drive. Indeed, they possess the ability to portray accurately the original performance at realistic sound levels, especially when coupled with powerful amplification.

## SYSTEM

Reflex transmission line loading floor standing

## DRIVE UNITS Bass Units

Two 172 mm loaded polypropylene cone with forward roll rubber surround and phase plug – long throw double wound coil on Kapton former with bump back magnet yoke

## Tweeter

19 mm soft dome ferro-fluid cooled

## CROSSOVER

Electrical 2 way second order network at 3 kHz – bi-wired

## FREQUENCY RANGE

35 Hz – 20 kHz

## SENSITIVITY

90 dB at 1 m for 1 watt

## IMPEDANCE

8 ohm nominal

## AMPLIFIER REQUIREMENTS

20 – 120 watts per channel

## DIMENSIONS

900 mm high (plus spikes provided) × 200 mm wide × 375 mm deep

## FINISH

Black Ash or Rosewood

## WEIGHT

21 Kg each (packed)